

NEW

SQ-1808/2508WS

Industrial Eco-friendly Special Solution Printer

KEUNDO 坤度



Speical Eco-friendly Digital Ink
C M Y K (Lc Lm Optional)

**1800
dpi**
Max Resolution

Variable Drop

Simple Operation


Continuous printing

4 x Gn5




CMYK x 2

6 x Gn5




CMYK x 3

8 x Gn5



CMYK x 4

12 x Gn5



CMYKLcLm x 4

>> Technical Characteristics

- Special eco-friendly digital ink that meets international standards, high color fastness, environmental-friendly, odorless;
- Automatic height measurement system;
- Use industrial print head technology, achieves high space(3.5mm), between print head and media, accept mode different media;
- Equipped with heating lamp on the 2 sides of head carriage, ensure color fastness;
- Equipped with front and rear Infrared drying and pre-heating system;
- Air-shaft take up system makes more stable media collecting;
- Stable printing technology and ink supply system reduces maintenance cost.

SQ-1808WS	4 x G5	6 x G5	8 x G5
4pass Production mode	80 m ² /h	120 m ² /h	160 m ² /h
6pass Quality model	55 m ² /h	80 m ² /h	110 m ² /h


SQ-2508WS	4 x G5	6 x G5	8 x G5
4pass Production mode	90 m ² /h	135 m ² /h	180 m ² /h
6pass Quality model	60 m ² /h	90 m ² /h	120 m ² /h

>> Technical Specifications

MODEL	SQ-1808WS	SQ-2508WS
PRINTHEAD TYPE	Ricoh Gen5	
HEAD NUMBER	Standard 4 heads (6/8/12 pcs optional)	
PRINTING SIZE (W)	1800mm	2500mm
PRINTING TECHNOLOGY	Gray scale piezoelectric inkjet technology	
PRINTING RESOLUTION	300X600dpi-2pass / 300X900dpi-3pass / 300X1200dpi-4pass / 300X1800dpi-6pass	
INK TYPE	Special Eco-friendly Digital Ink Continual Ink Supply Systems (2.5L Ink Tank) C/M/Y/K(Lc/Lm Optional)	
MEDIA THICKNESS	≤ 35mm	
COLOR CONTROL	ICC standard, adjustment of ICC and density	
RIP	PhotoPrint	
ENVIRONMENT	Temperature: 18°C-29°C, Humidity: 50%-80% (RH)	
POWER CONSUMPTION	Printing mode:10KW Sleep mode:600W	
PRINTER DIMENSION	3650 x 2450 x 1500 mm (With stand)	4300 x 2450 x 1550 mm (With stand)
PACKING WEIGHT	1.5T	2T

KEUNDO

Go Green, Go Eco, Go Soft, Go Keundo.



Yoga Mat



PVC Table Mat



Leather Floor Mat



PVC Terry Floor mat




Silicone Coaster




PVC plastic floor

Features



Automatic height measurement system, adjust the distance between the baseplate and the media automatically to guarantee the best quality. Increase the heating lamp on the 2 sides of head carriage, promote the drying of the printed media. Dual mute THK guide rails ensure stability of printing and high quality printing output. Rear Air-shaft media system, equipped with pre heating function, make sure the media get a better printing condition.



High-strength belt device, special high-strength low-stretch belt, no deviation, won't deform, long lasting. Adopt international standard ink supply system to ensure stable ink supply under high-speed printing. Automatic heads cleaning and moisturizing components make maintenance and operation more convenient. Front fan & infrared drying system, more effectively and quickly ensures the drying of printing medias!